

Series SSO Nomenclature

Examples

SSO-95-AA-M-GS...Micro Dual Row Offset Female, 95 contacts, Surface Mount Horizontal Tails, Mounting Holes, 2 Guide Posts

SSO-06-WD-12.0-C-LT...Micro Dual Row Offset Female, 6 contacts, 12.0" Color Coded 26 AWG Leadwire, 1 Top Latch

[] - [] - [] - [] - []

(Each option separated by a hyphen)

Series

SSO (Female)

Contacts

02 up to 97

Note:
Contact #s
less than 10,
use "0" first
ex: 02, 05, etc

Termination

PCB Tail Terminations

AA = SMH
H2 = Short/Long Alt.
DD = Straight
VV = SMV
FF = Flex

Wire Terminations

SS = Soldercup
WC = Cable*
WD = Discrete Leadwire
XX = Other*

Wire Length

(Skip if not wire term)

Length in Inches...
including tenths
example: 12.0
X.0 = Mixed Lengths

Common Options

(List in this order)

C = Color Coded Wire
M = Mtg Hole(s)
G = Guide Post Hole
GS = Multiple Guide Post Holes
LE = Latch (End mounted)
LES = Multiple Latches (Ends)
LT = Latch (Top mounted)
LTS = Multiple Latches (Top)
RoHS = RoHS Compliant

* Consult Factory