

	PART NO. A98033-009 REV ECO DATE APP
MATERIALS	A 106314 04-02-2020 TLM
HOUSING: ALUMINUM 6061, NICKEL PLATE (500 MICROINCHES MINIMUM) PER SAE-AMS-2404	
LATCH: STAINLESS STEEL, NICKEL PLATE PER SAE-AMS-2404	
INSULATOR: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138	FRONT OF CONNECTOR FLANGE
CONTACT: BERYLLIUM COPPER PER ASTM B194, C17200, GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CODE C, CLASS 1.27 TERMINATION:	0.026 (TYP) 0.66] 0.66] 0.050 (1.27] 0.050 0.050 0.127] 0.050 0
SOLDER COATED WITH SN63A PER J-STD-006 OR AMS-P- 81728	$\begin{array}{c} 2X & 0.092 \\ [2.34] \\ (4) \text{ SPACES } @ \\ .050 & = .200 \\ [1.27] & [5.08] \end{array}$
FRONT OF CONNECTOR	
	SUGGESTED HOLE PATTERN
ACTUAL SIZE	
TOLERANCES OWNETICS CONNECTOR CORP. THIS DOCUMEN	PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF T MAY NOT, IN WHICH OF IN PART, BE DUPLICATED, OR TITLE: (9) PIN MALE 90° BOARD MOUNT MICRO-D CONNECTOR MICRO-D CONNECTOR (9) PIN MALE 90° BOARD MOUNT MICRO-D PIN MALE 90° PIN MALE 90° P