

PART NO. A98033-512 APP REV ECO DATE 10446 05 - 16 - 18HV

MATERIALS

HOUSING:

ALUMINUM 6061, NICKEL PLATE (500 MICROINCHES MINIMUM) PER SAE-AMS-2404

LATCH:

STAINLESS STEEL, NICKEL PLATE PER SAE-AMS-2404

INSULATOR:


LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138


CONTACT:

BERYLLIUM COPPER PER ASTM B194, C17200, GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CODE C, CLASS 1.27

TERMINATION:

SOLDER COATED WITH SN63A PER J-STD-006 OR AMS-P-81728





NOTE:

DIMENSIONS IN [] ARE IN MILLIMETERS UNLESS OTHERWISE NOTED AND ARE FOR REFERENCE ONLY

Z	THIRD ANGLE⊕ ← -TOLERANCES-	HIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROF MANETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLI INSCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMMETICS CONNECTOR		
\Box	UNLESS OTHERWISE NOTED			
Ō	DIMENSIONS IN INCHES	DETM EDG	DATE 05 11 19	TITLE:
	2 DL DEC. 01	DI IIVI. LDO	05-11-16	(51) PIN MALE
7.0	2 PL DEC <u>+</u> .01		DATE	(01) 111111111
(()	3 PL DEC <u>+</u> .005	CHK,D		OOO DO A DD MOLINIT
D	4 PL DEC± .0005	CLIK D.		90° BOARD MOUNT
			DATE	
		ADD'D	D/112	MICRO-D CONNECTOR
ı≥	MINGELS # 1.	IAPP D.		MICKO D CONNECTOR

CONNECTOR CORPORATION A98033-512 7260 COMMERCE CIRCLE EAST MINNEAPOLIS, MN 55432 WWW.OMNÉTICS.COM

CS CAGE CODE 61873
DWG NO.

SHEET 2 OF 2 SCALE: 2: