

## ORDERING GUIDE



<b>1 Series</b>	<b>MNPO</b> Metal Nano Pin Offset	<b>MNSO</b> Metal Nano Socket Offset								
<b>2 Number Of Contacts</b>	<b>09</b>	<b>15</b>	<b>21</b>	<b>25</b>	<b>31</b>	<b>37</b>	<b>51</b>	<b>65</b>	<b>69</b>	<b>85</b>
<b>3 Termination Type</b>	<b>FF</b> Flex Tail									
<b>4 Shell Material &amp; Finish</b>	<b>N</b> Aluminum Shell, Electroless Nickel Plated					<b>CD</b> Aluminium shell, Cadmium Plated				
	<b>B</b> Aluminium Shell, Black Anodized					<b>S</b> Stainless Steel Shell, Passivated				
	<b>T</b> Titanium Shell, Unplated									
<b>5 Common Options</b>	<b>ETH</b> End Threaded Hole, #0-80					<b>EJS</b> End Jack Screw				
	<b>NTH</b> Non-Threaded Holes For Mounting To The Board									
	<b>YY</b> Non Standard Hardware (threaded holes, thumb screws, #2-56 screw)									
	<b>HT</b> High Temp. Epoxy					<b>RH</b> RoHS Compliant				
	<b>CS</b> Customer Supplied Material									
<b>6 Mod Codes</b>	<b>M10</b> Custom Keying					<b>M50</b> Space Grade Nano-D, SPT1				
	<b>M53</b> Space Grade Nano-D, SPT2									
<b>7 Special Instructions</b>	<b>YYY</b> Describe anything that is not covered in standard options									